

Dismounting of  
**BEARING & OTHER COMPONENTS**  
by **PRECISION**  
**HYDRAULIC PULLERS**



Series : PMP



**Fast, Safe & Economical Dismounting of Bearings & Other Components**  
**Precision Hydraulic Bearing Pullers with Inbuilt Hydraulic Pumps**


**SERIES PMP available in Range of 4 Tons to 30 Tons Capacity.**  
**2/3 jaws Hydraulic Pullers with Inbuilt Hydraulic Pump.**

## 2/3 JAW HYDRAULIC PULLERS WITH IN BUILT HYDRAULIC PUMP:



Model	Capacity	Stroke(mm)	Reach(mm)	Spread(mm)	Weight(kg)
PMP - 4	4 Ton	60	185	255	4.5
PMP - 6	6 Ton	60	185	255	4.5
PMP - 8	8 Ton	85	229	350	6.5
PMP - 10	10 Ton	85	229	350	6.5
PMP - 12	12 Ton	85	269	375	8.0
PMP - 15	15 Ton	85	269	357	8.0
PMP - 20	20 Ton	111	360	520	22
PMP - 25	25 Ton	111	360	520	22
PMP - 30	30 Ton	111	360	550	32

## 2 JAW HYDRAULIC BEARING PULLERS WITH IN BUILT HYDRAULIC PUMP:



Model	Capacity	Stroke(mm)	Reach(mm)	Spread(mm)	Weight(kg)
PM - 4	4 Ton	60	250	110	8.5
PM - 6	6 Ton	60	250	110	8.5
PM - 8	8 Ton	85	270	220	12.5
PM - 10	10 Ton	85	270	220	12.5
PM - 12	12 Ton	85	381	290	18.0
PM - 15	15 Ton	85	381	290	18.0

## 2/3 JAW HYDRAULIC PULLERS WITH IN BUILT HYDRAULIC PUMP CUM BEARING PULLER:



Model	Capacity	Stroke(mm)	Reach(mm)	Spread(mm)	Weight(kg)
PP - 4	4 Ton	60	185/250	255/110	4.5/8.5
PP - 6	6 Ton	60	185/250	255/110	4.5/8.5
PP - 8	8 Ton	85	229/270	350/220	6.5/12.5
PP - 10	10 Ton	85	229/270	350/220	6.5/12.5
PP - 12	12 Ton	85	269/381	375/290	8.0/18.0
PP - 15	15 Ton	85	269/381	375/290	8.0/18.0

### FEATURES :

- Self contained hydraulic pump and puller body with integral safety valve.
- 360 deg. Rotary Socket
- Four Stage of Foldable and removable handles saves the handle force during the operation.
- Easy release valve.
- Heat treated and chrome plated hydraulic cylinder rod provides linear force.
- 2/3 Combination puller cross head with manganese phosphate plated for rust proof and durability.
- Spring loaded live centering nut (removable).
- Heat treated forged alloy steel cross bolts and jaws with manganese phosphate plated.



P. O. Box No.: 7719, Borivali (W), Mumbai - 400 092.

Telefax: (022) 28145653.

Email: precisionia@precisioniaindia.com, precisionia@gmail.com

www.precisioniaindia.com, www.precisioninductionheater.com

**WORKS :** Unit No. 21, Dewan No. 6,  
Premises Co-op. Soc. Ltd., Navghar,  
Vasai (E), Thane - 401 210.

Telefax: 0250 - 2390307/ 2393589